

Military Charger - GS8002 Twin bay suitcase charger



The GS8002 charger is a Mil-Spec Charger for the BB-2590/U battery. It is designed in a rugged suitcase resistant to rough elements, EMI, Dust and field handling. It provides charge for 2 batteries simultaneously.

The GS8002 charger is able to provide safe and unattended charging and will automatically detect for defective cells. It is simple to use and can be operated by both DC and AC. A wide range of operating voltage input allows usage from any power source world wide / internationally.

Features

- 2 Battery Slots
- LED Indicators
- Compact Design
- Fast Charger
- Can be used in BB-590/U, BB-2590/U, BB-390/U
- Simple to use



Military Charger - GS8002 Specification

Specifications	
Part Number:	GS8002
Compatibility:	BB-2590/U, BB-590/U, BB-390/U
Dimension:	350mm x 310mm x 150mm
DC Input Range:	12 - 36VDC Mil-Spec 1275
AC Input Range:	95 - 260 V AC 47 to 440Hz
Charging rate:	2Amp per string
Charging Time:	Average 3.5h from flat battery BB-2590/U
Battery Slots:	2 per case
Indicators Lighted LED:	Fast Charge
Flashing:	Trickle Charge
No LED:	No Charge / complete
Weight:	4.3 kgs without batteries
Operational Temperature:	0° to 45°C
Storage Temperature:	-50°C to 65°C
Operational Altitude:	27000ft / 8300m
Storage Altitude:	55000ft / 16780m
Humidity:	95% relative

*Specifications are subject to change without prior notice.