

BA-3590/U Battery Pack

BA-3590/U is consists of high quality SAF™ Alkaline battery. The battery is designed and engineered to use in any military tactical operations.

- Printing on battery according to Mil-B-49030/10(E/R)
- High performance non-rechargeable Alkaline battery
- High reliability due to all welded construction
- Unit contains safety vented cells.

BA-3590/U meet the requirements of Mil-B-49030 for:

- Battery voltage
- Mechanical and thermal shock
- Electrolyte leakage
- Insulation test
- Vibration test
- Capacity test



Specifications	
Dimension:	111mm x 61.5mm x 126.5mm
For use in:	PRC-104, PRC-119, PRC-138, PRC-117F, KY-57 Singgars and other equipments.
Replacement for:	BA-5590/U, BA-5390/U, BA-5290/U, BB-490/U, BB-390A/U, BB-590/U, BB-2590/U
Operating Voltage:	12v / 24v
Nominal Voltage:	Two 12v per section
Nominal Capacity:	15Ah @ 15v / 7.5Ah @ 30v
Cell Type:	60 x AA Alkaline cells
Chemistry:	Alkaline
Casing Material:	Enforced ABS
Operating Temperature:	-20°C to +55°C
Storage Temperature:	-40°C to +55°C
Max Weight:	1.70kg
Disposal:	Check with local authorities

*Specifications are subject to change without prior notice.