

BB-590/U Battery Pack

BB-590 is High Performance rechargeable Nickel Cadmium battery.

Special Features

- Durable high impact ABS case
- Gold Plated contacts
- Optimal performance from Cell Selection
- Optional Diode Thermostats
- Slight Fire Retardancy
- Spring Activated Pressure Release valve

Testing Specifications

- Impact Tested
- Drop Tested
- Voltage Test
- Mechanical Shock Tested
- Vibration Tested
- Insulation Resistance
- Electrolyte Leakages
- Connector re-fittings [2000x]
- Cell selection



Specifications	
Nomenclature:	High Quality Nickel-Cadmium Cells
Nominal Displacement:	126.5mm x 111mm x 61.5mm
Nominal Weight:	1.40kg
Nominal Voltage:	24V or two 12V sections
Capacity:	2.4 Ah @ 24V 4.8Ah @ 12V
Terminals:	6 - hole socket, Gold plated pins
Operating Temperature Range:	-20°C to +55°C
Storage Temperature Range:	-20°C to +55°C
Applicable Military Spec:	Mil-B-49436B
Shelf Life:	5 years under controlled storage.
Case:	Mil-spec ABS, modified
Case Color:	Olive Drab Green / Khaki / Black
Alternative:	BA-5590, BB-390, BB-2590, BA-3590, BA-5390
Disposal:	Check with local regulations for proper disposal

*Specifications are subject to change without prior notice.